



**This commercial/
industrial door
is designed for
maximum thermal
efficiency and rugged
commercial uses.**

**10 YEAR
LIMITED
WARRANTY**

Commercial Model CS-300

- 2" thick sections.
- Foamed in place, polyurethane core.
- Thermally broken sections with tongue and groove joint construction.
- Options available to suit windload requirements.

Commercial/Industrial Model CS-300

- Monolithic plank sections, 18", 21" or 24" high.
- Microgrooved sections for commercial appearance.
- 26 gauge outside, 27 gauge inside steel skins.
- Polyurethane foamed in place insulation R-value 14.3.
- 24 gauge galvanized steel reinforcement plates at hinge locations.
- Tongue and groove joints thermally broken.
- 2" thick sections.
- Options available to suit windload specifications.
- Available in white and brown.
- 10 year limited warranty, see separate warranty sheet for complete details.

Weather tight
tongue-and-groove


Micro-grooved
section with deep
woodgrain texture

Insulation 95% closed
cell urethane

26 gauge front
and 27 gauge back
for sturdiness and
added rigidity



Protective Factory Applied Paint System



- 1 .75 mil. finish coat
- 2 .25 mil. primer
- 3 Galvanizing
- 4 Steel

Paint Process

Paint process includes a hot dipped .25 mil primer with rust inhibitor then a coating of .75 mil baked on polyester paint.

Color Options

Available in white and brown.



new england door★usa

New England Door, LLC 15 Campanelli Circle, Canton, MA 02021-2480
Tel. 800-969-5151 ■ 781-821-2737 ■ Fax 781-821-8050
E-mail us at mail@nedoor.com ■ www.nedoor.com
Specifications of product are subject to change without notice.